

**SeeSnake Video Inspection Systems & Accessories**

- RI-13998 SeeSnake Plus Self-Leveling 325 ft. Color Reel**  
2" to 12" Lines up to 325 ft.; 2" 90s, 3" P-traps  
Includes an always upright, self-leveling camera design  
Flexible transmitter for easy locating; fully compatible with NaviTrack II & NaviTrack Scout  
Can be used with CS6 or CS10 monitor
- RI-14063 Mini SeeSnake Plus 200 ft. Mini Color Reel**  
1-1/2" lines up to 200 ft.; 1-1/2" 90s, 2" P-traps  
Improved push cable & smaller camera head to push farther through tighter spots  
Flexible transmitter for easy locating; fully compatible with NaviTrack II & NaviTrack Scout  
Can be used with CS6 or CS10 monitor  
\* Also available with self-leveling camera option
- RI-37468 65 ft. MicroDrain Inspection System with Sonde**  
Small Diameter & Tight Turn Radius camera head to get through toilet traps & 1" lines  
Multiple Monitor Compatibility allows you to use the microDrain reel with your SeeSnake monitor or the microEXPLORER™ Digital Inspection Camera  
Can be used with any SeeSnake monitor or recorder
- RI-35133 L100 Micro Reel with Sonde**  
For use with Seesnake monitor or microExplorer Digital Inspection Camera  
Sonde transmitter technology for locating the camera head position when in the line  
Interchangeable Drums let you change out the inner drum depending on the application  
Can be used with any SeeSnake monitor or recorder
- RI-40008 nanoReel Industrial Inspection Camera System**  
Small Diameter and Tight-Turn Radius camera allows 3/4" lines up to 85 feet to be inspected  
Interchangeable Drums let you change out the inner drum depending on the application  
Can be used with any SeeSnake monitor or recorder
- RI-39338 CS10 Digital Recording Monitor**  
Includes 2 batteries & 1 charger  
One-Touch Recording for recording to a USB thumb drive, in a computer-readable format.  
12.1" Daylight Readable Display for easily monitoring inspections in bright outdoor environments  
3 Modes of Recording lets you take digital stills, full frame video, & compressed video format
- RI-45143 CS6 Digital Recording Monitor**  
Includes 1 battery  
Capture still images & video clips directly to USB drive; generate high quality multi-media reports  
Compatible with all SeeSnake camera reels; Screen is readable in daylight
- RI-37888 CA-300 Micro Inspection Camera**  
Includes 3 ft. cable w/ 17 mm Imager, battery, charger, USB cable, hook, magnet and mirror accessories, RCA cable, AC adapter, headset with microphone, 4Gb SD card.
- RI-36738 CA-100 Micro Inspection Camera**  
Includes 3 ft. cable w/ 17 mm Imager  
Allows you to perform more detailed visual inspections in even harder-to-reach areas  
Comfortable pistol-grip design, one-hand controls, and large screen make it easy to see



**SeeSnake Video Inspection Systems & Accessories**

RI-20973

**4" Induction Clamp**

The RIDGID Inductive clamp allows users to apply a signal to a cable or pipe when connecting directly to the target conductor is not possible. The clamp couples the transmitting signal onto the conductor which then allows users to locate using a compatible receiver, such as the NaviTrack™ or NaviTrack Scout™. Two built in LED's inform the user the clamp is functioning properly. An integrated adapter allows users to attach a hotstick for out of reach lines. Compatible with both the NaviTrack 10 Watt Transmitter & the NaviTrack Brick Transmitter.



RI-22163

**SR-60 Line Locator**

Can trace any frequency from 10 Hz to 490,000 Hz. Can trace energized lines and sondes (active beacons) simultaneously. Target Line – Guides the operator down the line and shows changes in direction. Left-Right Guidance Arrows – Points the operator to the target utility. Proximity Signal and Signal Strength – Helps the operator center the locator closer to the target for more confident locates.



RI-21893

**SR-20 Line Locator**

Target Line – Guides the operator down the line and shows changes in direction. Left-Right Guidance Arrows – Point the operator to the target utility. Proximity Signal and Signal Strength – Helps the operator center the locator closer to the target for more confident locates. Continual Depth – Increases productivity by showing depth changes in real time. Current Strength – Identifies current on target line for faster diagnosis of complex locates.



RI-21903

**ST-510 10-Watt Transmitter**

Direct Connect using attached Clips  
Induction from the optional Inductive Signal Clamp  
Induction from the Transmitter Coils

**DriveKore is the only Authorized SeeSnake Repair Center  
in the Central PA Region.  
We also offer on-site SeeSnake demonstrations and training.**

[Click here for the YouTube videos](#)