



Maximum initial battery voltage (measured without a workload) is 12, 20 and 60. Nominal voltage is 10.8, 18 and 54. 120V MAX is based on using 2 DEWALT 60V MAX* lithium-ion batteries combined. DEWALT's Perform & Protect[™] line of Power Tools is designed to provide a high level of one or more of the following: control, dust containment, or low vibration, without sacrificing performance. **Terms and Conditions:** This is not a game of chance. Void where prohibited. Offer only available at participating DriveKore retail location. Offer valid on purchases made from 10/1/17 through 10/31/17, while supplies last. All federal, state and local laws and regulations apply. Redemption items will be provided at the participating retail location following the purchase, after receipt of original invoices. DriveKore and DEWALT reserve the right to limit number of redemptions per customer and/or transaction. DEWALT reserves the right to provide alternate redemption items of equal or greater value. Offer valid only for product end users. Amounts on flyer do not include taxes. Offer not valid with any other offer or promotion. Offer subject to change without notice. No cash value.

Copyright ©2017 DEWALT. The following are examples of trademarks for one or more DEWALT power tools and accessories: the yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool. MF DriveKore Fall 090817.ai/KS/GDS/17-526764