

Carbide Core Bits

Taper Fit Shanks (Adapters)

| | Type | Drilling Depth | Price |
|-------------|---------|----------------|---------|
| RE-SMXTL-10 | SDS Max | 10" | \$40.75 |
| RE-SMXTL-18 | SDS Max | 18" | \$45.65 |
| RE-S02TL-10 | Spline | 10" | \$34.15 |
| RE-S02TL-18 | Spline | 18" | \$40.75 |



Heavy Duty Core Bits

| | Size | Price |
|-------------|--------|----------|
| RE-CBT-32HO | 2" | \$122.40 |
| RE-CBT-40HO | 2-1/2" | \$163.20 |
| RE-CBT-48HO | 3" | \$188.70 |
| RE-CBT-64HO | 4" | \$330.35 |
| RE-CBT-80HO | 5" | \$357.00 |



Carbide core bits provide an economical alternative to diamond core bits when working in clean concrete or block. Instead of the investment and hassle of using a core rig, carbide core bits can be attached to a rotary hammer drill. This makes them a more portable solution for smaller jobs. Also, no water is required.

Starter Points (Pilot Drills)

| | Size | Price |
|------------|--------|---------|
| RE-CBSP-32 | 2" | \$22.95 |
| RE-CBSP-40 | 2-1/2" | \$22.95 |
| RE-CBSP-48 | 3" | \$22.95 |
| RE-CBSP-64 | 4" | \$25.45 |
| RE-CBSP-80 | 5" | \$25.45 |



3 Components... (Once the hammer core bit has been used, the shank and core bit become a one-piece system)

1. TAPER FIT SHANK



SPLINE or SDS-max Shank
(other shank styles & lengths available on request)

2. HEAVY-DUTY CORE BIT



6" Body Length
4-1/2" Core Depth
Carbide teeth can be replaced or sharpened.

3. STARTER POINT



Heat-Treated, Spring-Loaded

• No stress points

• Tapered Shank • No knock-out hole for pilot

Extra-thick core body wall • Extra-length core body • Core Bits made from solid steel

DRIVEKORE

101 Wesley Drive • Mechanicsburg, PA 17055 • Phone: (717) 766-7636 • Toll-Free (800) 382-1311
Fax: (717) 697-7477 • Toll-Free Fax: (800) 739-1101 • Email: orders@DriveKore.com

www.DriveKore.com