



# STI Toilet Flange Firestop Gasket

**OVERVIEW** ✓

US Patent No. 7,694,474 B1


## Stop Flushing Profits Down The Drain.

Firestop your closet flange applications with the SpecSeal® Closet Flange Firestop Gasket and get out of the bathroom quickly

SpecSeal® Closet Flange Firestop Gaskets are a one-piece, molded rubber, intumescent pad that installs beneath a 3" or 4" (76 or 102 mm) closet flange to effectively firestop the opening. The die cut rubber gasket is perforated to delineate removable inserts sized to accommodate various outer diameters of toilet flanges.

Traditional firestop methods require the firestop material to be applied around the pipe prior to setting the flange. If the firestop material is not sufficiently recessed, the flange will not fit.

The alternative is to apply the firestop material from the bottom. This necessitates the use of ladders, costly lifts, and more labor



SpecSeal® Closet Flange Firestop Gaskets are an easy, cost-effective, code-compliant solution!

**\$14.76**

#STI-CF34



INSTALLS FROM THE TOP

**APPLICATIONS** ✓

SpecSeal® Closet Flange Firestop Gaskets are designed to allow the drain pipe connected to a toilet flange to be properly firestopped without the need for firestop caulk for typical floor assemblies with plastic or metal pipes.

**PERFORMANCE** ✓

SpecSeal® Closet Flange Firestop Gaskets have been successfully tested in accordance with ASTM E814 (ANSI/UL1479) and CAN/ULC-S115 in one and two hour fire-rated floor assemblies. Consult factory for individual system designs and application requirements.

**QUICK. EASY. ECONOMICAL** ✓

- Seamless fit for fast, easy installation with no tools required
- Lower installed cost
- Foolproof installations
- Work from the top, not from a lift below the floor
- No caulk to clean up
- Always ready to use. No shelf life. No caulk tubes to dry out.
- UL Classified. Code compliant

**PHYSICAL PROPERTIES** ✓

Thickness	1/4" (6 mm)
Weight	0.13 lbs (0.06 kg)
Expansion Begins	320°F (160°C)
Volume Expansion	800%
Storage Temperature	Less than 120°F (49°C)
Shelf Life	No Limit

**3<sup>RD</sup> PARTY APPROVALS** ✓



Fill, void or cavity materials for use in through-penetration firestop systems. See UL Fire Resistance Directory. 8L98

**ORDERING INFORMATION** ✓

Part #	Description	Case Qty.
CF34	3" or 4" (76 or 102 mm) trade size closet flange gasket	10

MADE IN USA



# DRIVEKORE

101 Wesley Drive • Mechanicsburg, PA 17055 • Phone: (717) 766-7636 • Toll-Free (800) 382-1311  
Fax: (717) 697-7477 • Toll-Free Fax: (800) 739-1101 • Email: orders@DriveKore.com

www.DriveKore.com